in guar com		4
jaquar.com Document No.		JAQUAT BATH+LIGHT
SNW/OPS/24/753S250UFPMZ		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	- -150	385
+150-+ 455+ P-trap can be converted to S-trap 250mm using convertion bend.		
17		
Ø16-/	35	
TOP VIEW	SIDE VIEW	BACK VIEW
Conoral Information		
General Information		
Product Code	OPS-WHT-15753S250UFPMZ	
Brand	ladnau	
Colour	White	
Туре	Complete Set For Coupled WC (S-Trap)	
Material	Ceramic-Vitreous China (VC)	
Product Specification		
Product Dimension	385x680x785 mm	
Basin Inner Dimension	260X335 mm	
Product Net Weight	51.0 kg.	
Product Gross Weight	59 kg	
Packaging Dimension	870x500x430 mm	
Outlet	Vertical	
Waste Hole Distance	University distance between the Flore and the centre line of the works outlet hole < 250 years	
	Horizontal distance between the Floor and the centre line of the waste outlet hole \leq 250 mm	
	Rimless Bowl With Cistern For	
Product Features	Coupled WC With UF Soft Close Seat Cover, Hinges, Dual Flush-3/6 LPF	
	With Conversion Bend - ZPS-WHT-VB02	
	Anti Germ Glaze, Trap glazed.	
ACCESSORIES INCLUDED		
UF Soft Close Seat cover	OPS-WHT-15101UFPM	
Floor Fixing Screw	ZPS-SNS-FB02	
Cistern	OPS-WHT-15201CPM	
Cistern Fittings	ZCF-WHT-FT015	
Wax Seal	ZPS-WHT-1401	
Conversion Bend	ZPS-WHT-VB02	
CARE AND CLEANING GUIDELINES		
- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.		
¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.		
¬ Carefully inspect the new product for damage before installation.		
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.		
¬ Risk of external leakage. Do not lift or rock the bowl after placement.		
¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.		
¬ Do not allow cleaners to sit or soak on the product.		
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.		
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.		
Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.		
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.		
QUALITY MANAGEMENT SYSTEM - ISO 9001		
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All		
dimensions are in mm (Tolerance \pm 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product		