



| | |
|---|---|
| Product Code | ALD-CHR-649K |
| Description | Exposed Part Kit of Concealed Thermostatic valve for Health Faucet (Compatible with ALD-649C) |
| Flow Rate | 18.76 LPM @ 3 bar |
| Recommended Water Pressure | 0.2 Bar- 5 bar |
| Brass Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> |
| Specification | <ul style="list-style-type: none"> • Thermostatic cartridge to regulate the temperature. • Thermostatic cartridge made from high quality polymer that resists scale build-up. • The cartridge confirms to European norms, NF EN 1111. In case of cold water cut, the disposal of hot water shall not exceed 200 ml in 0-5 sec. • WRAS Approved European Thermostatic Cartridge • Standard temperature range 15°C to 60°C. • Highest level of Convenience • Protected against backflow. |
| Finish | Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass) |
| Available Colour Finishing | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Dust (GDS), Auric Gold (GLD), Gold Matt PVD (GMP), Graphite (GRF), Stainless Steel (SSF) & White Matt (WHM) |
| * As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy | |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. | |