





| Product Code | OPP-CHR-15115PM |
|-----------------------------------|---|
| Description | Single Lever Wall Mixer with Provision for Connection to Exposed Shower Pipe (SHA- |
| | 1211N) with Connecting Legs & Wall Flanges |
| Flow Rate | 20.50 LPM @ 3 bar |
| Flow regulator | By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate. |
| Recommended Water Pressure | 0.5 Bar - 5 Bar |
| Brass Specification in Percentage | Brass Ingots as per IS:1264-1997 |
| | Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total |
| | Impurity (0.0-2.0), Zn (Remainder) |
| | Brass Rod as per IS:319-1989 |
| | Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) |
| | Brass Sheets as per IS:410-1977 |
| | Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder) |
| Cartridge Specification | Cartridge with Temperature Limiter |
| | Cartridge with Brass Spindle |
| | Life Cycle EN 817: 70,000 cycles (Standard) |
| | - 2.1 LAC Cycles as per EN 817* |
| | - 10.5 LAC Cycles (ON/OFF)* |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| Finish | Plating: Nickel-10.0 micron Chromium-0.3 micron |
| | Salt Spray (500 hrs + Validated) |
| | Adhesion (Pass) |
| Aerator Size | WRAS, ACS Approved (24X1) |
| | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD |
| Available Colour Finishing | (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Dust (GDS), Auric Gold (GLD), Gold Matt PVD (GMP), Graphite (GRF), Stainless Steel (SSF) & White Matt (WHM) |
| | IMART 1 VD (GIVII), GIAPITICE (GIVI), Statitiess Steel (SSI) & WITHE MART (WITH) |

* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.