



Single Lever Exposed Shower Mixer for Connection to Hand Shower with Connecting Legs & Wall Flanges  32.00 LPM @ 3 bar  0.5 Bar - 5 Bar
32.00 LPM @ 3 bar
0.5 Bar - 5 Bar
0.0 50.1
Brass Ingots as per IS:1264-1997
Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total
Impurity (0.0-2.0), Zn (Remainder)
Brass Rod as per IS:319-1989
Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Brass Sheets as per IS:410-1977
Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
Cartridge with Temperature Limiter
Cartridge with Brass Spindle
Life Cycle EN 817: 70,000 cycles (Standard)
- 2.1 LAC Cycles as per EN 817*
- 10.5 LAC Cycles (ON/OFF)*
16 bar (Pass)
25 bar (Pass)
Plating: Nickel-10.0 micron Chromium-0.3 micron
Salt Spray (500 hrs + Validated)
Adhesion (Pass)
Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold
Dust (GDS), Auric Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)

\* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.