





Product Code	OPP-CHR-15173BPM
Description	Single Lever Sink Mixer with Swinging Spout (Table Mounted) with 450mm Long Braided
	Hoses
Connection Size	Braided hoses, 1/2" FIP (WRAS Approved)
	Withstand pressure of 10 Bar
Flow Rate	16.25 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM,
	GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
	or one in the contract of the
Recommended Water Pressure	0.5 Bar - 5 Bar
	Brass Ingots as per IS:1264-1997
	Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total
	Impurity (0.0-2.0), Zn (Remainder)
Brass Specification in Percentage	·
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
	Brass Pipe as per IS:407-1996
	Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)
Cartridge Specification	Cartridge with Temperature Limiter
	Cartridge with Brass Spindle
	Life Cycle EN 817: 70,000 cycles (Standard)
	- 2.1 LAC Cycles as per EN 817*
Water Tieleter on	- 10.5 LAC Cycles (ON/OFF)*
Water Tightness Pressure Resistance	16 bar (Pass)
Pressure Resistance	25 bar (Pass) Plating: Nickel-10.0 micron Chromium-0.3 micron
Finish	Salt Spray (500 hrs + Validated)
	Adhesion (Pass)
Aerator Size	WRAS, ACS Approved (24X1)
Aciator Size	
Available Colour Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold
	Dust (GDS), Auric Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt
	(WHM)

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.