

jaquar.com Document No. SNW/ITS/24/853P180PPPMAT










SIDE VIEW





ITS-WHT-89853P180PPPMAT
Jaquar
White
Automatic Rimless Floor Mounted WC
Ceramic - Vitreous China
390x685x465 mm
270X340 mm
48 kg.
54 kg
700x480x590 mm
Horizontal
Vertical distance between the Floor and the center line of the waste outlet hole ≤ 180 mm
• Single flush – 4.5LPF,Power Rated Supply – 220V-240V, 50-60 Hz,Rated Power – 1100 W • Heater Power – Air Dryer - 200 W, Warm water – 1600 W, Seat – 50W,• Wireless Remote (RF) & IPx4 (Water resistance) • Sensor Activate Seat Cover – Auto opening ,Seat & Cover • Adjustable Seat Temperature – 30/34/37°c • Adjustable Water Temperature – 34/36/38°c • Adjustable Air Temperature – Room temperature – 55°c • Auto Flush • Anti-Bacterial Seat/Nozzle/Ceramic • LED Night Light • Air Dryer • Foot Button • Front & Rear Wash Nozzle with Oscillation mode.• Smart Button and Remote Control • Instant Heating Technology • Smart flushing and powerful flushing with low noise • Slim in shape - Seat thickness is 6.5cm • UV nozzle and Self cleaning • Deodorization - Cold catalyst
ITS-WHT-89111AT
ZPS-WHT-ST59

CARE AND CLEANING GUIDELINES

Remote

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.

ZPS-WHT-ST01B

- \neg Carefully inspect the new product for damage before installation.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- $_{
 eg}$ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- \neg Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product