General Information Product Code Brand Colour White Type Wall H Material Ceram Product Specification Product Dimension	SIDE VIEW BACK VIEW WHT-37953BIUFSM r
SNW/DRS/24/953BIUFSM	VHT-37953BIUFSM
525 450 525 5000 10000	VHT-37953BIUFSM
450 Image: Constraint of the second seco	VHT-37953BIUFSM
450 Image: Constraint of the second seco	VHT-37953BIUFSM
450 Image: Constraint of the second seco	VHT-37953BIUFSM
General Information Product Code DRS-V Brand Jaqua Colour White Type Wall H Material Ceran Product Specification 355x5 Bowl Opening (Inner Dimension) 250x3 Product Net Weight 29.5 k	VHT-37953BIUFSM
Product Code DRS-V Brand Jaqua Colour White Type Wall H Material Ceran Product Specification 355x5 Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	r
Brand Jaqua Colour White Type Wall H Material Ceran Product Specification 250X3 Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	r :
Colour White Type Wall H Material Ceran Product Specification 255x5 Bowl Opening (Inner Dimension) 250x3 Product Net Weight 29.5 k	
Type Wall H Material Ceran Product Specification Product Dimension 355x5 Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	
Material Ceran Product Specification 7000000000000000000000000000000000000	lung WC
Product Specification Product Dimension 355x5 Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	
Product Dimension 355x5 Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	nic - Vitreous China
Bowl Opening (Inner Dimension) 250X3 Product Net Weight 29.5 k	
Product Net Weight 29.5 k	25x380 mm
	35 mm
Product Gross Weight 34.5 k	g.
	g
Packaging Dimension 540x4	50x400 mm
Outlet Horizo	ontal
Intern	al diameter of inlet hole dia. Ø 58 \pm 3 mm
Inlet And Outlet Hole Dimension	The diameter of outlet hole dia. ϕ 100 ± 5 mm
Product Features Modern Design with Rectangular Shape	
Blind Installation	om wall tile surface to center of seat cover fixing hole
Anti Bacterial Glaze on Ceramic Smooth Glaze Surface ,Material - Vitreous China (VC)	while windle to center of seat cover fixing note
UF Slim Soft Close Seat Cover (La) W	/C Fixing wall thickness
Water Usage - 3/6 LPF With Wash Down Flushing (Lb) Flushing	rom wall tile surface to the inner bowl
Anti Bacterial Seat Cover Product With Complete Genuine Accessories	te of WC
Complete Trap Wash, Rimless Design	
ACCESSORIES PROVIDED	ULT 20101UL
	VHT-39101UF /HT-GK01
	/HT-FB13
ACCESSORIES RECOMMENDATION	
	NS-RB07N
Concealed cistern JCS-W CARE AND CLEANING GUIDELINES	HT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.	
¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.	
¬ The product is neavy and it is recommended that two persons not it with ¬ Carefully inspect the new product for damage before installation.	
¬ Calcium inspect the new product for damage before instantion. ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.	
	UI VILICUUS UIIIIId.
 Risk of external leakage. Do not lift or rock the bowl after placement. Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface. 	
Do not allow cleaners to sit or soak on the product.	
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	