

TOP VIEW	SIDE VIEW BACK VIEW
GENERAL INFORMATION	
Product Code	CNS-WHT-961NSPP
Brand	Jaquar
Colour	White
Туре	Wall Hung WC
Material	Ceramic-Vitreous China (VC)
PRODUCT SPECIFICATION	
Product Dimension	380X555X360 mm
Bowl Opening (Inner Dimension)	280x335 mm
Product Net Weight	22.8 kg
Product Gross Weight	28 kg
Packaging Dimension	435 X395 X590 mm
Outlet	Horizontal
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole Ø 55 +3/-1 mm
	External diameter of outlet hole dia. Ø 100 \pm 5 mm
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 210 mm
PRODUCT FEATURES	
Product Features	Rimless Wall Hung WC, PP Soft Close Seat Cover
	Dual Flush - 4.5/3 LPF Dual & I Flush advantages
	Complete Trap Glaze, Anti Germ Glaze.
ACCESSORIES INCLUDED	
Seat Cover	CNS-WHT-115S
Inlet & Outlet gasket	ZPS-WHT-GK01
ACCESSORIES RECOMMENDATION	
Rag bolt	ZPS-MST-RB07N
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
Rag bolt	

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \neg Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- eg Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- \neg Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \neg Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- ¬ Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product.Last modified on 25 March 2025.