



<b>Product Code</b>	OHS-CHR-85857
<b>Description</b>	<p>Alive- Maze Prime Single Function Shower 450 X 350mm AISI 304 stainless steel with RGB LED light remote control &amp; installation kit for false ceiling</p> <ul style="list-style-type: none"> <li>Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz</li> </ul>
<b>Flow Rate</b>	47.00 LPM @ 3 bar
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Mount Type</b>	Ceiling Mounting
<b>Spray Modes</b>	Single Function
<b>Material Composition Specification in Percentage</b>	<p><b>STAINLESS STEEL:</b> Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)</p> <p><b>ABS:</b> Specific Gravity (g/cm<sup>2</sup>) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102</p>
<b>REMOTE CONTROL</b>	
<b>LED POWER SUPPLY</b>	<ul style="list-style-type: none"> <li><b>CHROMO THERAPY (RGB)</b> • LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz</li> <li><b>COLOR VARIATION</b> •</li> </ul> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Mono Color (RGB)</p> </div> <div style="text-align: center;"> <p>Chromo Therapy</p> </div> </div> <p style="text-align: center;">LED On / Off Switch Sensor by Remote Control</p>
<b>Technology</b>	<b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
<b>Registered design no.</b>	276014
<b>Finish</b>	Salt Spray (350 hrs + Validated) Adhesion (Pass)
<b>Available Finishing</b>	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Graphite (GRF) & Stainless Steel Finish (SSF)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.