



Product code	SNR-CHR-51085C
Description	Concealed Installation Box for Urinal Sensor Consisting of Solenoid Valve with Control Valve (But without Exposed Part Kit)
Water Supply	Single line
Water Temperature	5 °C - 65 °C
Inlet/Outlet Water Connection	1/2" BSP / 15mm
Water Discharge per Flush	Pre- Flush - 1.3 LPF (Liter Per Flush) @ 3 Bar Post Flush - 3.2 LPF (Liter Per Flush) @ 3 Bar
Ideal Operating Water Pressure	1.0 – 3.0 bar
Solenoid Valve Specification	Ideal Operating Water Pressure : 1.0 -3.0 Bar Input rated voltage supply: DC-6V IPX7 Protected : Very robust, reliable solenoid valve Low power consumption : Bi-stable pulse controlled
Material Composition Specification in Percentage	Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity(0.0-0.7), Zn(Remainder) ABS - Specific Gravity (g/cm ²) - (1.06-1.10), Melt Mass Flow Rate (g/10 min.) - (20-26), Rockwell Hardness - (95-115), DTUL @ 66 psi (0.45 MPa) (0C) - (78-102)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	