jaquar.com	JAQUAL BATH+LIGHT
Document No.	0
SNW/LYS/24/801/305	
	490
590-EQ-EQ-EQ-	
Ø35- O	
045-	
	F.F.Lyl.
L 500 500	http://www.commence.com/commence.com/commence.com/commence.com/commence.com/commence.com/com/com/com/com/com/com/com/com/com/
TOP VIEW	
I OF VIEW	SIDE VIEW BACK VIEW
General Information	
Product Code	LYS-WHT-38801 + LYS-WHT-38305
Brand	Jaquar
Colour	White
Туре	Wall Hung Basin with half pedestal
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	590x490x185 With Pedestal 400 mm
Basin Inner Dimension	500x335x125 mm
Product Net Weight	Basin 13.8.0 kg. pedestal 6 kg
Product Gross Weight	Basin 15.5 kg pedestal 6.7 kg
Packaging Dimension	Basin 615X200X500 mm Pedestal 280X260X340 mm
Outlet	Vertical
	Tap hole dia. Ø 35 ± 2 mm
Tap Hole And Outlet Hole Dimension	Internal diameter of outlet hole dia. Ø45 +2/-1 mm
	Horizontal distance between the centre line of the tap hole and the centre line of the waste outlet hole \leq 125
Product Features	With tap hole and over flow hole cap, Anti germ glaze .
ACCESSORIES INCLUDED	
Basin fixing screw	ZPS-MST-RB03
Brass overflow hole Cap	ZPS-WHT-9012B
ACCESSORIES RECOMMENDATION	
Half Pedestal	LYS-WHT-38305
Fixing Screw	ZPS-MST-FB05
CARE AND CLEANING GUIDELINES	
	ucts are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use
thereafter.	
- The product is heavy and it is recommended that two persons hold it while it is being fixed.	
— Carefully inspect the new product for damage before installation.	
¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.	
-, Risk of external leakage. Do not lift or rock the bowl after placement.	
¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
¬ Do not allow cleaners to sit or soak on the product.	
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
DISCLAIMER: Our every effort has be	en made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or
countries. All dimensions are in mm	(Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
# For Installation Refer Actual Produ	ct de la constant de