



<b>Product Code</b>	JCS-WHT-2400WP
<b>Description</b>	Single Piece Slim Concealed Cistern With Wall Mounting Frame, Installation Kit And "P-Type" Drain Pipe Connection Set For Wall Hung Wc (Without Flush Control Plate)
<b>Flow Rate</b>	3.0/6.0 LPF
<b>Features</b>	<ul style="list-style-type: none"> <li>• <b>Tank body:</b> Strong 80 mm thick High-density polyethylene (HDPE) 'Single-piece' body.</li> <li>• <b>Anti-Condensation Lining:</b> Anti condensation lining of 6mm thick wall takes care of temperature change.</li> <li>• <b>Inlet &amp; Outlet Valves:</b> Inlet valve has a special rotary structure which gives out low noise &amp; anti siphon function. Both valves (Inlet &amp; outlet) are WARS approved.</li> <li>• <b>Working Pressure:</b> 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water supply)</li> <li>• <b>Life Cycles of Mechanism:</b> The lifetime of sea water test and dirty water test have passed 100,000 cycles</li> <li>• <b>Flush Control Plates:</b> ABS made chrome plated flush control plates which is compatible for Single Piece Slim in-wall Cistern (JCS-WHT-2400WP)</li> <li>• <b>Wall Mounted Frame:</b> oxford blue Powder coated steel frame.</li> <li>• <b>Water inlet:</b> ½" water supply connection from top.</li> <li>• <b>Flush volume:</b> Factory setting 6.0~3.0 litres, Eco adjustable: 4.0~2.0 litres (Only for WC pans designed for low volume flushing).</li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li>• For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres</li> <li>• Solid pre-wall installation system for brick &amp; solid walls</li> <li>• For installation in a load bearing stud wall.</li> <li>• Not suitable for installation in a drywall</li> </ul>
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	