



|   |  |
|---|--|
| <b>Product Code</b>   | ALD-CHR-069FT  |
| <b>Description</b>  | Reduced body of concealed stop cock suitable for 15mm pipe line with plastic protection cap (without Exposed Parts)  |
| <b>Flow Rate</b>  | 47.00 LPM @ 3 bar  |
| <b>Recommended Water Pressure</b>   | 0.5 Bar - 5 Bar  |
| <b>Material Composition Specification in Percentage</b>   | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> |
| <b>Cartridge Specification</b>  | <p>Cartridge Specification = M24X1.5P (Approx. 3/4"), Multi/Full turn Cartridge.<br/>Life Cycle = 2Lac.<br/>Max.Hot Water 90°( Recommended 65°)<br/>Grease Quality = Klubersynth VR 69-252 N to be used.<br/>Washer Quality = Rubber NBR type to be used.</p>  |
| <b>Water Tightness</b>  | 16 bar (Pass)  |
| <b>Pressure Resistance</b>  | 25 bar (Pass)  |
| <b>Available Colour Finishing</b>   | CHROME (CHR)   |
| * As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy  |  |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |  |