



|  |  |
|--|--|
| <b>Product Code</b>                      | ALD-CHR-783N   |
| <b>Description</b>                       | Aquamax Concealed Body of Single Lever Shower Mixer with 3-way diverter, But without Exposed Parts   |
| <b>Flow Rate</b>                         | 54.15 LPM @ 3 bar  |
| <b>Recommended Water Pressure</b>        | 0.2 Bar- 5 bar   |
| <b>Brass Specification in Percentage</b> | <p><b>Brass Ingots as per IS:1264-1997</b><br/>Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> |
| <b>Cartridge Specification</b>           | <p>Cartridge with Temperature Limiter<br/>Cartridge with Brass Spindle<br/>Life Cycle EN 817: 70,000 cycles (Standard)<br/>- 2.1 LAC Cycles as per EN 817*<br/>- 10.5 LAC Cycles (ON/OFF)*</p>   |
| <b>Finish</b>                            | <p>Plating: Nickel-10.0 micron Chromium-0.3 micron<br/>Salt Spray (500 hrs + Validated)<br/>Adhesion (Pass)</p>  |
| <b>Available Colour Finishing</b>        | CHROME (CHR)   |

\* As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.