





| Product Code | SPJ-CHR-7429 |
|-----------------------------------|---|
| Description | Bath Tub Spout with Wall Flange |
| Flow Rate | 47.00 LPM @ 3 bar |
| | By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 |
| Flow regulator | LPM, GB-8.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the |
| | flow rate. |
| Recommended Water Pressure | 0.5 Bar - 5 Bar |
| | Brass Ingots as per IS:1264-1997 |
| | Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total |
| | Impurity (0.0-2.0), Zn (Remainder) |
| | |
| Brass Specification in Percentage | Brass Rod as per IS:319-1989 |
| | Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) |
| | Brass Sheets as per IS:410-1977 |
| | Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder) |
| Water Tightness | 16 bar (Pass) |
| Pressure Resistance | 25 bar (Pass) |
| | Plating: Nickel-10.0 micron Chromium-0.3 micron |
| Finish | Salt Spray (500 hrs + Validated) |
| | Adhesion (Pass) |
| Aerator Size | WRAS, ACS Approved (M 28X1) |
| | Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), |
| Available Colour Finishing | Gold Dust (GDS), Auric Gold (GLD), Graphite (GRF), Stainless Steel (SSF) & White Matt |
| | (WHM) |
| | 1, , |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.