





OPP-CHR-15213BPM
Single Lever 1-Hole Bidet Mixer with Popup Waste System with 375mm Long Braided
Hoses
Braided hoses, 1/2" FIP (WRAS Approved)
Withstand pressure of 10 Bar
7.15 LPM @ 3 bar
By using flow regulators (Product should be ordered with suffix as GA-6.0 LPM @ 3.0 Bar
pressure) one can regulate the flow rate.
0.5 Bar - 5 Bar
Brass Ingots as per IS:1264-1997
Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total
Impurity (0.0-2.0), Zn (Remainder)
Brass Rod as per IS:319-1989
Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Brass Sheets as per IS:410-1977
Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
Cartridge with Temperature Limiter
Cartridge with Brass Spindle
Life Cycle EN 817: 70,000 cycles (Standard)
- 2.1 LAC Cycles as per EN 817*
- 10.5 LAC Cycles (ON/OFF)*
Pop-up waste 1¼"
16 bar (Pass)
25 bar (Pass)
Plating: Nickel-10.0 micron Chromium-0.3 micron
Salt Spray (500 hrs + Validated)
Adhesion (Pass)
WRAS, ACS Approved (18x1)
Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD
(BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Dust (GDS), Auric Gold (GLD), Gold

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussani, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.