jaquar.com	1 torus
Document No.	JAQUAR BATH+LIGHT
SNW/VGS/24/953UF	
	570 570 570 570 FFLVI. FFLVI. BACK VIEW
General Information	SIDE VIEW
Product Code	VGS-WHT-81953UF
Brand	
Colour	Jaquar White
Type Material	Wall Hung WC
	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	390X570X365 mm
Bowl Opening (Inner Dimension)	250x355 mm
Product Net Weight Product Gross Weight	29 kg
	35 kg
Packaging Dimension	590x440x410 mm
Outlet	Horizontal
Outlet Hole Dimension	Internal diameter of inlet hole Ø 58 ± 3 mm
	External diameter of outlet hole dia. Ø 100 \pm 5 mm
Product Features	Rimless bowl design, Heavyduty seat cover, Anti germ glazing. Best suitable for bigger bathrooms
ACCESSORIES PROVIDED	·
Seat Cover	VGS-WHT-81101UF
Inlet & Outlet gasket	ZPS-WHT-GK01
Side cap	ZPS-WHT-SC01
ACCESSORIES RECOMMENDATION	ZPS-MST-RB07
Rag bolt Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
CARE AND CLEANING GUIDELINES	
and use thereafter.	
- The product is heavy and it is recommended that two persons hold it while it is being fixed.	
Carefully inspect the new product for damage before installation.	
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Risk of external leakage. Do not lift or rock the bowl after placement.	
Risk of external leakage. Do not lift or rock the bowl after placement.	
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
- Do not allow cleaners to sit or soak on the product.	
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
 Wipe surfaces clean and rinse completely with water immediately after applying cleaners. Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent 	
- Clean Chrome, stamless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stamless steel. If used, finse the surface immediately to prevent corrosion.	
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	