



TOP VIEW



SIDE VIEW



BACK VIEW


**GENERAL INFORMATION**

Product Code	LAS-WHT-91953BIUFSM
Brand	Jaquar
Colour	White
Type	Wall Hung WC
Material	Ceramic-Vitreous China (VC)

**PRODUCT SPECIFICATION**

Product Dimension	370x530x360 mm
Bowl Opening (Inner Dimension)	275x335 mm
Product Net Weight	24.8 kg.
Product Gross Weight	30.3 kg.
Packaging Dimension	460 X 410 X 555 mm
Outlet	Horizontal
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. $\varnothing$ 55+3/-1 mm
	External diameter of outlet hole dia. $\varnothing$ 100 $\pm$ 5 mm
	Vertical distance between the Floor and the centre line of the waste outlet hole $\leq$ 225 mm

**PRODUCT FEATURES**

Rimless Wall Hung WC with Blind Installation UF Soft Close Slim Seat Cover Dual Flush - 6/3 LPF Anti Germ Glaze.	<b>(L) From wall tile surface to center of seat cover fixing hole</b>  <b>(La) WC Fixing wall thickness</b>  <b>(Lb) From wall tile surface to the inner bowl surface of WC</b>	
---	---	---

**ACCESSORIES INCLUDED**

UF Soft Close Seat Cover	LAS-WHT-91101UF
Inlet outlet Gasket	ZPS-WHT-GK01
Fixing kit	ZPS-WHT-FB13

**ACCESSORIES RECOMMENDATION**

Rack bolt	ZPS-SNS-RB07N
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS

**CARE AND CLEANING GUIDELINES**

→ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
→ The product is heavy and it is recommended that two persons hold it while it is being fixed.
→ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
→ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
→ Risk of external leakage. Do not lift or rock the bowl after placement.
→ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
→ Do not allow cleaners to sit or soak on the product.
→ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
→ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
→ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
→ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
→ Recommended to use Genuine Accessories.

**QUALITY MANAGEMENT SYSTEM - ISO 9001**

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance  $\pm$  5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.

# For Installation Refer Actual Product. Last modified on 25 March 2025.