

Date: 11/09/2024 Revision No.: 01

# LED COLT FOCUS LIGHT SURFACE 15 W

Indoor Luminaire Product Code:-AKL-BLK-CTFCBR15AC15SW, AKL-BLK-CTFCBR26AC15SW, AKL-BLK-CTFCBR36AC15SW, AKL-BLK-CTFCBR60AC15SW AKL-BLK-CTFCBR15AC15SN, AKL-BLK-CTFCBR26AC15SN, AKL-BLK-CTFCBR36AC15SN, AKL-BLK-CTFCBR60AC15SN 15W - 1050Lm - 3000K - CRI>90 - Beam Angle - Available in 15,26,36,60°



### **Technical Specifications**

	•	
Ор	perating Temperature(°C)	-10°C to 40°C
Ra	ted Input Voltage & Frequency	230 VAC, 50Hz
Ra	ted Input Wattage (W)	15W ± 10%
Ra	ted Input Current (A)	0.068 A (Nominal)
Po	wer Factor (PF)	0.90
AT	HD (%)	<10 %
Ra	ted Luminous Flux	>1050 lm (tolerance as per BIS)
Ra	ted Luminaire Efficacy	>70 lm/W (tolerance as per BIS)
Со	rrelated Color Temperature (CCT)	3000 K, 4000K (tolerance as per ANSI)
Со	lor Rendering Index (CRI)	>90 Ra
Be	am Angle	Available in 15 ,26, 36, 60° (Deg)
Dri	iver Efficiency (%)	>85 %
LE	D Life Span	>50000 Hrs (Ta=25°C @L70)
Le	ns / Reflector	Lens
Mc	punting	Surface mount
Protections		
Ov	er Voltage Protection	Withstand upto 440V/AC for 4 Hrs.
Su	rge Protection	±4.0KV
Pro	otection Class	Class II
Ing	press Protection (IP Rating)	IP20
Im	pact Protection (IK Rating)	IK02
Sh	ort Circuit Protection	Provided
Ор	en Circuit Protection (No Load)	Provided
Re	everse Polarity Protection	Provided

# Product Dimensions:- (LXWXH)

125X77X95 mm (Tol. ± 5 mm)



## **Applications**

Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.

With our continuous efforts to upgrade the technology/product, all product specifications and data are subject to change without prior notice. We always try to maintain the accuracy of our product images, but due to different viewing conditions, the colors may vary. Images are only for indicative purpose.