

LED COLT FOCUS ZOOM SURFACE LIGHT 15 W

Indoor Luminaire

Product Code:-

AKL-BLK-CTFCBRZMAC15SW, AKL-BLK-CTFCBRZMAC15SN

15W - 1050Lm / 975 Lm - 3000K - CRI>90 - Beam Angle - Adjustable Btw (min) 22 °- 42°(max)



Technical Specifications

| | |
|------------------------------------|--|
| Operating Temperature(°C) | -10°C to 40°C |
| Rated Input Voltage & Frequency | 230 VAC, 50Hz |
| Rated Input Wattage (W) | 15W ± 10% |
| Rated Input Current (A) | 0.068 A (Nominal) |
| Power Factor (PF) | 0.90 |
| ATHD (%) | <10 % |
| Rated Luminous Flux | Narrow >1050 lm / Wide > 975 lm (tolerance as per BIS) |
| Rated Luminaire Efficacy | Narrow > 70 lm/W / Wide > 65 lm/W (tolerance as per BIS) |
| Correlated Color Temperature (CCT) | 3000 K, 4000K (tolerance as per ANSI) |
| Color Rendering Index (CRI) | >90 Ra |
| Beam Angle | Adjustable Btw (min) 22 °- 42°(max) (Deg) |
| Driver Efficiency (%) | >85 % |
| LED Life Span | >50000 Hrs (Ta=25°C @L70) |
| Lens / Reflector | Lens |
| Mounting | Surface Mount |




Protections

| | |
|-----------------------------------|-----------------------------------|
| Over Voltage Protection | Withstand upto 440V/AC for 4 Hrs. |
| Surge Protection | ±4.0KV |
| Protection Class | Class II |
| Ingress Protection (IP Rating) | IP20 |
| Impact Protection (IK Rating) | IK02 |
| Short Circuit Protection | Provided |
| Open Circuit Protection (No Load) | Provided |
| Reverse Polarity Protection | Provided |

Product Dimensions:- (LXWXH)

130X77X95 mm (Tol. ± 5 mm)



Applications

Residences, Offices, Small Retail Shops,
Hotels, Coffee Shops, Restaurants, Hospitals,
area lighting and for other indoor applications.

With our continuous efforts to upgrade the technology/product, all product specifications and data are subject to change without prior notice. We always try to maintain the accuracy of our product images, but due to different viewing conditions, the colors may vary. Images are only for indicative purpose.