





Product Code	OPP-CHR-15193NKPM
	Single Lever 3-inlet Diverter Exposed parts kit Consisting of Operating Lever, Cartridge
Description	Sleeve, Wall Flange (with Seals), Button Assembly Sleeve and Button Cap (Compatible with
	ALD-193N)
Recommended Water Pressure	0.5 Bar - 5 Bar
	Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Brass Specification in Percentage	
	Brass Sheets as per IS:410-1977
	Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)
	Plating: Nickel-10.0 micron Chromium-0.3 micron
Finish	Salt Spray (500 hrs + Validated)
	Adhesion (Pass)
	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD
Available Colour Finishing	(BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP), Graphite (GRF) &
	Stainless Steel (SSF).

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.